

The most Advanced Grease Gunsone designed to suit each application. Exclusively from Lumax[®]



Agricultural, Automotive, Fleet, Heavy-Duty Trucks, Industrial, Construction, Mining



- Balanced and Ergonomic Design
- Lightweight and Durable
 Construction
- Comfortable, Non-Slip Grip
- Chrome Plated Barrel for Maximum Protection against Corrosion
- Ideal for hard-to-reach
 Grease Fittings
- Maximum Operating Pressure: 7,000 PSI (483 bar)
- High Flow Rate: 3.5 oz./min. (95g/min.)
- Built-in Pressure Relief Valve
- Powerful 1500mAh Ni-Cd Battery Pack
- Fully Charged Battery Delivers up to 5 Cartridges of Grease

Ergonomic Design: Relieves Fatigue while Speeding-up Routine Lubrication Tasks





LX-1176 Two Batteries







HandyLuber comes with everything you need including:

- Pressure Relief Valve
- 30" Ultra-flex Hose with Spring Guards and Non-Drip Cap
- · Hose and Coupler Holder
- 90~132V 1-hour Fast Charger
- High Capacity, 12 Volt Ni-Cd Battery Pack
- Compact Slim-Line Carrying Case

LIGHTWEIGHT. COMPACT. ERGONOMIC. BALANCED.





RoboLuber sets a new standard in Heavy-duty Cordless Grease Gun Performance. The Power to lubricate just about Anything, Anytime, Anywhere!



- Two-speed Switch for High-Pressure or High-Volume Delivery
- Continuous Operation with High Pressure Delivery
- Patented Configuration: Speeds up Routine Unique Lubrication Tasks
- Highly Efficient Power Transmission: Permits Faster, more Effective Lubrication
- Versatile Refilling with 2-way Loading: Cartridge or Bulk
- Comfortable Grip and Balanced Design
- Heavy-Duty, Durable Construction
- Chrome Plated Barrel for Maximum Protection against Corrosion
- Maximum Operating Pressure: 10,000 PSI (690 bar)
- Powerful 1500mAh Li-ion Battery Pack
- Fully Charged Battery Delivers more than 6 Cartridges of Grease
- High Flow Rate: 7 oz./min. (200g/min) at Normal Pressure 2.8 oz./min. (80g/min) at High Pressure

RoboLuber comes with everything you need including:

- Integrated LED Light to find hidden Grease Points
- Pressure Adjustable Switch
- Pressure Relief Valve
- 30" Ultra-flex Hose with Spring Guards
- Hose Holder
- Anti-fatigue Carrying Strap
- 100~240V 1-hour Fast Charger
- 2 pcs. High Capacity 20 Volt Li-Ion Battery Packs
- Convenient Pocket to store Manual
- Compact Slim-Line Heavy Duty Carrying Case



FAST. EFFICIENT. POWER. PERFORMANCE.

Dual-Leverage, Premium Pistol Grease Gun with 18" (450mm) High Pressure, Ultra-flex Hose

LX-1153

- Balanced and Ergonomic Design
- Convenience of One-hand operation for easy Greasing
- Exclusive Dual-Leverage Feature for Pressure or Volume Output
- Maintains Pressure and Grease flow in Confined Spaces
- Heavy-duty LuCast[™], Cast-Alloy Head
- Develops up to 8,500 PSI (586 Bar)
- Handy 3-way Loading:
 Standard Cartridge, Suction or Bulk fill
- 18" High-Pressure Ultra-Flex Hose with Spring Guard for Hard-to-reach Fittings
- Rugged Chrome plated finish Handle and Barrel for Maximum Protection against Corrosion
- Deluxe Oil-resistant, Contoured Grip for Comfort and Sure-handed Grip
- Equipped with Air Bleeder Valve to vent Air Pockets in the Grease Chamber
- Heavy Gauge Steel Barrel (18G/1.3 mm)
- Wide Band Non-slip Knurling for Sure-grip Handling
- Tough Full-molded Follower allows a
 Superior Seal and eliminates Grease bypass
- Heavy-duty Follower Spring for Consistent Priming
- Posi-lock Follower Rod with Ergonomically designed T-handle provides Positive Grip and Easy Filling at any position
- Four Hardened Jaws Heavy-Duty Coupler
- Output: Volume Mode: 4 oz. (115g)/100 Strokes. Pressure: 2,850 PSI (196 Bar)

Pressure Mode: 2 oz. (57g)/100 Strokes. Pressure: 8,500 PSI (586 Bar)



© 2016 Lumax[®]. All Rights Reserved. Lumax[®] and the products described in it are copyrighted by Lumax[®] with all Rights Reserved. 02/16/5K Tel: 803-548-3000 Fax: 803-547-0800





Push-Lube Grease Gun 3 oz. (85g) Capacity

- Multi-functional
- One-hand Operation. Compact Grease Gun
 get grease into tight spaces
- All-purpose Nozzle for Hydraulic & Ball-head Grease Fittings and Pointed Nozzle for Cup-shaped Grease Fittings
- High-quality, Shock-resistant Plastic. Withstands changes in Temperature
- Transparent Body for Visual Control of Fill Level
- Suitable for High Viscosity Oils and Greases of up to Medium Consistency (NLGI #2)
- Delivery Rate: 0.5g/Stroke
- Comes with Universal Connector (M10x1), Conical Nozzle & Non-drip Protective Cap
- Ideal for Lubricating Standard Grease Fittings in Lawn Mowers, Chain Saws, Outboard Motors, Boat Trailers, ATVs, Snowmobiles, Mountain Bikes, Pick-Up Trucks, and Golf Course Equipment



Lumax®

USA













